

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
28 March 2002 (28.03.2002)


PCT

(10) International Publication Number
WO 02/25594 A1

- (51) International Patent Classification⁷: **G06T 15/30** (74) Agents: **HALSNE, Eric** et al.; Honeywell International Inc., 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US).
- (21) International Application Number: PCT/US01/23739
- (22) International Filing Date: 27 July 2001 (27.07.2001) (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- (25) Filing Language: English
- (26) Publication Language: English Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
— entirely in electronic form (except for this front page) and available upon request from the International Bureau
- (30) Priority Data:
60/233,153 18 September 2000 (18.09.2000) US
- (71) Applicant: **HONEYWELL INTERNATIONAL INC.** [US/US]; Law Department, 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US).
- (72) Inventor: **CONNER, Kevin**; 726 Alvord Ave N., Kent, WA 98031 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **TRAPEZOIDAL REDUCTION OF POLYGONS AND INTERRUPTED POLYGONS**



(57) Abstract: A method, system, and computer program product for rendering an image to available display area based on parameters of one or more unusable display areas. The method includes determining one or more trapezoids for defining the available display area based on the parameters of the one or more unusable display areas. After an image is generated, the method determines if the generated image is within the determined one or more trapezoids, and renders the components of the generated image that are determined to be located within the one or more trapezoids.



WO 02/25594 A1

5

TRAPEZOIDAL REDUCTION OF POLYGONS AND INTERRUPTED POLYGONS

10

BACKGROUND OF THE INVENTION

Typically, an enhanced ground proximity warning system (EGPWS) must rapidly
15 determine if EGPWS created objects are to be displayed on a display that may have
overlaid polygons, thereby reducing the available area of the display. The easiest method
for defining the available area is through the creation of a bitmap (i.e., white is
inside/black is outside). However, the present method, which uses triangles to define the
area, can not perform this in real-time while the aircraft is in flight. Therefore, a real-time
20 drawing method is needed.

SUMMARY OF THE INVENTION

The present invention comprises a method, system, and computer program
product for rendering an image to available display area based on parameters of one or
more unusable display areas. The method includes determining one or more trapezoids
25 for defining the available display area based on the parameters of the one or more
unusable display areas. After an image is generated, the method renders the components
of the generated image that are determined to be located within the one or more
trapezoids.

In accordance with further aspects of the invention, determining the one or more
30 trapezoids includes generating lines that define a boundary around the available display
area. Once the boundary is defined, the method eliminates all lines being parallel to a
predefined scan line direction and sets a first flag for each line to the lines maximum

coordinate in a first axial direction. The first axial direction is orthogonal to the scan line direction. The method then sorts the remaining lines into a list according to a sorting scheme. Then, the method generates a trapezoid based on the first two lines in the list and the next highest flag value of all the flags, and replaces the flag of the first and second
5 lines with the next highest flag. If the first flag for the first or second line is equal to the minimum coordinate of the respective line on the axis orthogonal to the scan line direction, the method eliminates that line. The method repeats until all lines are eliminated.

In accordance with other aspects of the invention, sorting includes setting a
10 second flag for each line to a coordinate associated with the first flag in a second axial direction, the second axial direction being orthogonal to the first axial direction. The sorting scheme places lines with the highest first flag value first in the list and if lines have the same first flag value, places the line with the lower second flag value first in the list.

As will be readily appreciated from the foregoing summary, the invention
15 provides a method, system, and computer program product for rendering an image to an available display area based on parameters of one or more unusable display areas.

BRIEF DESCRIPTION OF THE DRAWINGS

The preferred and alternative embodiments of the present invention are described
20 in detail below with reference to the following drawings.

FIGURE 1 is a front view of a display showing unusable and available display areas;

FIGURE 2 is a front view of a display showing the available display area from
FIGURE 1;

FIGURES 3 and 4 are flow diagrams illustrating the process of the present
25 invention; and

FIGURE 5 is an example illustrating a complex display with useable and available areas.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The present invention provides a method, apparatus, and computer program
30 product for rapidly defining available display area and displaying content within the defined available display area. Typically, a display process sends information to a display as long as the information is determined to be within a displayable area of the display. An example display is an enhanced ground proximity warning system (EGPWS) display that
35 is present in many commercial and non-commercial aircraft. Many avionic display

manufacturers now produce displays that include masked areas that are used for presenting various textual information. As a result, the remaining area is the only available area for displaying other information, such as EGPWS, radar, weather, or other types of avionic information. Other types of display manufacturers may also produce
5 restricted area displays that, like the avionic displays, require some processing in order to determine if a generated image is to be rendered.

FIGURE 1 illustrates an example display 20 provided by a manufacturer. The display 20 includes information presentation areas (unusable areas) 22-26, which produces an available area 28. The manufacturer provides for the presentation of various
10 information in these areas 22-26. The present invention provides a process for quickly and easily defining the available area 28 for effectively rendering other display information therein. Display users (e.g., a pilot) sometimes are provided with display mode options that allow the user to select which area 22-26 or combination of areas 22-26 to display. The method of the present invention performs real-time analysis of a newly
15 selected display mode to define the available area 28. FIGURE 2 further illustrates the available area 28 from FIGURE 1. Once the available area 28 is defined, an application program renders an image into only the defined area 28.

FIGURE 3 illustrates a preferred process of the present invention. First, at block 50, the present invention receives information regarding the areas of the display previously designated and not for use by any other application sharing the display. Next,
20 at block 52, the process determines a set of trapezoids that define the available area of the display. This step is described in more detail below in FIGURE 4 and by example in FIGURE 5. Then, at block 54, the application program that is designated to use the available area generates an image. Finally, at block 56, the process renders the generated
25 image onto the display based on the determined set of trapezoids.

FIGURE 4 shows an embodiment for determining a set of trapezoids, from block 52 of the process shown in FIGURE 3, for a display that renders images with horizontal scan lines. First, at block 60, with respect to the available area after the pre-designated area information is considered, the process defines all lines that define the
30 boundary of the available area. Then, at block 62, the process discards all horizontal lines. Next, at block 64, for the remaining lines, set current Y to the maximum value of Y (Y_{max}) for the respective line and set current X to the X value at Y_{max} . At block 66, the lines are sorted first from $Y_{max} - Y_{min}$ (i.e., maximum to minimum of current Ys). If there are lines with identical current Ys, then they are sorted from $X_{min} - X_{max}$ (i.e.,
35 minimum to maximum of current Xs).

Next, the process defines the trapezoids that describe the available area, see blocks 68-72. A first trapezoid is defined by making a horizontal line from the highest sorted current Y to the next line (i.e., from the top of the first sorted line to the top of the second sorted line). At block 70, the bottom of the first trapezoid is defined by using the Y of next highest current Y and making a horizontal line from the first line in the sorted list to the next intersecting line (may not be the second line in the sorted list). At block 72, the edge line segments of the first trapezoid are then found as those portions of the first and second line segments that connect the ends of the horizontal top and bottom lines. At block 74, the process updates the current Y of the first and second sorted line to the next highest current Y. Next, at decision block 76, the process checks whether the updated current Y is the same as the minimum Y value (Y min) for either the first or second line after the list is resorted. If the check at decision block 76 is not satisfied, then the process returns to block 66 and continues until all the lines have been eliminated. If the check at decision block 76 is true for the first and second line, then the line, where the updated and minimum Y are the same, is eliminated from the sorted list. At block 80, the process described above continues until all the lines are eliminated from the sorted list.

FIGURE 5 illustrates an example display where everything within the M-shaped object is available for use by an application. The M-shaped object is composed of points A, B, C, D, E, F, G, H, J, K, L, M, and N which form lines AB, BC, CD, DE, EF, FG, GH, HJ, JK, KL, LM, MN, and NA. The trapezoid defining process proceeds as follows:

- 1) The algorithm first discards all lines that are horizontal (or vertical if processing in the Y). This eliminates lines AB, DE, and FG.
 - 2) The remaining lines are reset such that their current Y is set to the lines Max Y and the current X is set to the X for the Max Y.
 - 3) The lines are sorted by current Y(max...min) and current X(min ... max)
CD, EF, NA, BC, JK, GH, LM, KL, MN
 - 4) Find next highest current Y.
 - 5) The first pair forms a trapezoid with the base of the object set to the next highest current Y. This yields line segments 128 and 130.
 - 6) The defined trapezoid is rendered.
 - 7) The current Ys of CD and EF are updated to the next highest Y (i.e. the base of the trapezoid). If the new current Y is the Min Y for the line, the line is eliminated.
 - 8) Repeat steps 3-7 until all lines are eliminated.
- The progression is as follows:
- Lines CD, EF, NA, BC, JK, GH, LM, KL, MN. Render trapezoid with line segments 128 and 130;

Lines NA, BC, CD, EF, JK, GH, LM, KL, MN. Render trapezoid with line segments 101 and 136;

Lines CD, EF, NA, BC, JK, GH, LM, KL, MN. Render trapezoid with line segments 127 and 131;

5 Lines NA, BC, CD, JK, GH, EF, LM, KL, MN. Render trapezoid with line segments 102 and 135;

Lines CD, JK, GH, EF, NA, LM, KL, BC, MN. Render trapezoid with line segments 132 and 115;

10 Lines GH, EF, NA, LM, KL, BC, CD, JK, MN. Render trapezoid with line segments 117 and 126;

Lines NA, LM, KL, BC, CD, JK, GH, EF, MN. Render trapezoid with line segments 103 and 108;

Lines KL, BC, CD, JK, GH, EF, NA, LM, MN. Render trapezoid with line segments 109 and 134;

15 Lines CD, JK, GH, EF, NA, LM, KL, MN. Render trapezoid with line segments 133 and 114;

Lines GH, EF, NA, LM, KL, JK, MN. Render trapezoid with line segments 140 and 125;

20 Lines NA, LM, KL, JK, GH, EF, MN. Render trapezoid with line segments 104 and 107;

Lines KL, JK, GH, EF, MN, LM. Render trapezoid with line segments 110 and 113;

Lines GH, EF, MN, LM, KL, JK. Render trapezoid with line segments 118 and 124;

25 Lines MN, LM, KL, JK, GH, EF. Render trapezoid with line segments 105 and 106

Lines KL, JK, GH, EF. Render trapezoid with line segments 111 and 112; and

Lines GH, EF. Render trapezoid with line segments 119, 120, 122 and 123.

30 Once all the trapezoids have been defined, a display processor determines if pixels of an image to be displayed are within one of the trapezoids. The display processor scans all of the lines of the rendered trapezoids. The processor then sorts the lines, gathering those lines where the target Y value falls between the Ymax value and the Ymin value. The processor discards all others. For each pixel defined as (Xtarget, Ytarget), the processor compares the Xtarget value to the X value on a given line at Ytarget. The result
35 is that the X value on that line is either greater than, less than or equal to Xtarget.

For each time the X value on the line equals the Xtarget value, the processor assigns a zero. Greater values receive a 1 value and lesser values a -1. As the processor cumulates a total across each scan line, values of 0 as a cumulative total across the line to a given point define the line as being inside of the desired trapezoid. All other values are outside. Coloring the points accordingly, the processor has accomplished the fill task.

The examples shown above are for use with a horizontal scanline display system. This process can also be used with a vertical scanline display system by changing Y for X and X for Y.

The following is an alternate embodiment for determining if an image element is within a reduced-size displayable area. First, all active lines or boundary lines are scanned. In a horizontal scanline display system, each display element is given a value depending upon the number of scanned lines that have been crossed in a scanline progression through the display elements of a target Y value. For example, referring to FIGURE 2, if display element locations 34 and 38 have the same Y value, then all display locations along the scanline are given a -1 value until a boundary line is reached. After a first boundary line is crossed a 1 value is added to the display locations that follow the first boundary line, thereby assigning a 0 value for those locations. At the next boundary line encountered, a -1 value is added to the display locations that follow that next boundary line, thereby assigning a -1 value for those locations. The alternately adding a 1 and -1 value continues until the end of the scanline. After the above analysis, any image elements (smallest components of a generated image) are displayed only if the display element location has an assigned 0 value, otherwise the image element is not displayed.

While the preferred embodiment of the invention has been illustrated and described, as noted above, many changes can be made without departing from the spirit and scope of the invention. Accordingly, the scope of the invention is not limited by the disclosure of the preferred embodiment. Instead, the invention should be determined entirely by reference to the claims that follow.

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. A method for rendering an image to available display area based on parameters of one or more unusable display areas, the method comprising:
 - 5 determining one or more trapezoids for defining the available display area based on the parameters of the one or more unusable display areas;
 - generating an image;
 - determining location of components of the generated image relative to the determined one or more trapezoids; and
 - 10 rendering the components of the generated image that are determined to be located within the one or more trapezoids.
2. The method of Claim 1, wherein determining comprises:
 - a) generating lines that define a boundary around the available display area;
 - 15 b) eliminating all lines being parallel to a predefined scan line direction;
 - c) setting a first flag for each line to the lines maximum coordinate in a first axial direction, the first axial direction being orthogonal to the scan line direction;
 - d) sorting the remaining lines into a list according to a sorting scheme;
 - 20 e) generating a trapezoid based on the first two lines in the list and the next highest flag value of all the flags;
 - f) replacing the flag of the first and second lines with the next highest flag;
 - g) if the first flag for the first or second line is equal to the minimum coordinate of the respective line on the axis orthogonal to the scan line direction,
 - 25 eliminating that line; and
 - h) repeating d-g until all lines are eliminated.
3. The method of Claim 2, wherein sorting comprises:
 - 30 setting a second flag for each line to a coordinate associated with the first flag in a second axial direction, the second axial direction being orthogonal to the first axial direction;
 - wherein the sorting scheme places lines with the highest first flag value first in the list and if lines have the same first flag value, place the line with the lower second flag value first in the list.
- 35 4. A computer program product for performing the method of Claim 1.

5. A computer program product for performing the method of Claim 2.
6. A computer program product for performing the method of Claim 3.
7. A system for rendering an image to available display area based on parameters of one or more unusable display areas, the system comprising:
 - 5 a means for rendering an image to available display area based on parameters of one or more unusable display areas, the computer program product comprising:
 - a means for determining one or more trapezoids for defining the available display area based on the parameters of the one or more unusable display areas;
 - 10 a means for generating an image;
 - a means for determining location of components of the generated image relative to the determined one or more trapezoids; and
 - a means for rendering the components of the generated image that are determined to be located within the one or more trapezoids.
 - 15
 8. The system of Claim 7, wherein the means for determining comprises:
 - a means for generating lines that define a boundary around the available display area;
 - a means for eliminating all lines being parallel to a predefined scan line direction;
 - 20 a means for setting a first flag for each line to the lines maximum coordinate in a first axial direction, the first axial direction being orthogonal to the scan line direction;
 - a means for sorting the remaining lines into a list according to a sorting scheme;
 - a means for generating a trapezoid based on the first two lines in the list and the next highest flag value of all the flags;
 - 25 a means for replacing the flag of the first and second lines with the next highest flag;
 - if the first flag for the first or second line is equal to the minimum coordinate of the respective line on the axis orthogonal to the scan line direction, a means
 - 30 for eliminating that line; and
 - a means for repeating until all lines are eliminated.
 9. The system of Claim 8, wherein the means for sorting comprises:

a means for setting a second flag for each line to a coordinate associated with the first flag in a second axial direction, the second axial direction being orthogonal to the first axial direction;

5 wherein the sorting scheme places lines with the highest first flag value first in the list and if lines have the same first flag value, place the line with the lower second flag value first in the list.

10. A system for rendering an image to available display area based on parameters of one or more unusable display areas, the system comprising:

10 a first component configured to render an image to available display area based on parameters of one or more unusable display areas, the computer program product comprising:

a second component configured to determine one or more trapezoids for defining the available display area based on the parameters of the one or more unusable display areas;

15 a third component configured to generate an image;

a fourth component configured to determine location of components of the generated image relative to the determined one or more trapezoids; and

a fifth component configured to render the components of the generated image that are determined to be located within the one or more trapezoids.

20

11. The system of Claim 10, wherein the means for determining comprises:

a generating component configured to generate lines that define a boundary around the available display area;

25 an eliminating component configured to eliminate all lines being parallel to a predefined scan line direction;

a first flag component configured to set a first flag for each line to the lines maximum coordinate in a first axial direction, the first axial direction being orthogonal to the scan line direction;

30 a sorting component configured to sort the remaining lines into a list according to a sorting scheme;

an image means component configured to generate a trapezoid based on the first two lines in the list and the next highest flag value of all the flags;

a second flag component configured to replace the flag of the first and second lines with the next highest flag;

if the first flag for the first or second line is equal to the minimum coordinate of the respective line on the axis orthogonal to the scan line direction, an eliminating component configured to eliminate that line; and
a repeating component configured to repeat until all lines are eliminated.

5

12. The system of Claim 11, wherein the sorting component comprises:

a setting component configured to set a second flag for each line to a coordinate associated with the first flag in a second axial direction, the second axial direction being orthogonal to the first axial direction;

10

wherein the sorting scheme places lines with the highest first flag value first in the list and if lines have the same first flag value, place the line with the lower second flag value first in the list.

15






Fig.1.


2/5

*Fig. 2.*

3/5

*Fig. 3.*

4/5

*Fig. 4.*




Fig. 5.

INTERNATIONAL SEARCH REPORT

Intern Application No

PCT/US 01/23739

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G06T15/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06T

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, INSPEC, IBM-TDB, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 521 210 A (IBM) 7 January 1993 (1993-01-07) column 5, line 2 - line 21; claim 1	1,4,7,10
X	EP 0 344 686 A (OKI ELECTRIC IND CO LTD) 6 December 1989 (1989-12-06) column 4, line 35 - line 51 column 6, line 36 -column 7, line 47	1,4,7,10



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

4 February 2002

Date of mailing of the international search report

11/02/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Burgaud, C

INTERNATIONAL SEARCH REPORT

Information on patent family members

Internat Application No

PCT/US 01/23739

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0521210	A	07-01-1993	EP 0521210 A1	07-01-1993
			CA 2069116 A1	06-01-1993
			DE 69132068 D1	27-04-2000
			DE 69132068 T2	05-10-2000
			JP 2096907 C	02-10-1996
			JP 5150930 A	18-06-1993
			JP 8012587 B	07-02-1996
			US 6005574 A	21-12-1999
EP 0344686	A	06-12-1989	JP 1304588 A	08-12-1989
			DE 68926263 D1	23-05-1996
			DE 68926263 T2	28-11-1996
			EP 0344686 A2	06-12-1989
			US 4972330 A	20-11-1990